



Endo Spring Balancer 0.5 - 1.5Kg Cap. 1.0M Travel

SKU: EK-0

- Capacity Range: 1.1 to 3.3 lbs. (0.5 to 1.5 kg)
- Cable Travel: 3.28 ft. (1.0 m)
- Cable Diameter: 0.12 in. (3.0 mm)
- Unit Weight: 1.1 lbs. (0.5 kg)
- Width: 5.0 in. (127 mm)
- Depth: 1.9 in. (48.2 mm)
- Length (hook to hook I.D.): (236 to 1237 mm)

PRODUCT DESCRIPTION

- Secondary Support: Includes a top support eyelet to accommodate a safety chain.
- High impact cast ABS plastic housing.
- Easy and precise ratchet system spring adjustment.
- Zero-Gravity tool holding with no drifting or strain.
- Tapered drum, quality springs, and ball bearings provide smooth cable travel throughout the stroke.
- CE mark available (European Conformity)

Choosing the Right Spring Balancer:

Size the balancer to carry the total weight of the tool and all accessories to be balanced.

Use the upper end of the capacity range of the balancer when possible. For example, if the total tool weight is 10.5 lbs, a balancer with a capacity range of 5.5-11.0 lbs would be a better choice than one with a range of 9.9-19.8 lbs.

Choose the cable travel length that best suits your application.

Note: This model does not have a fall arrest system to prevent the tool/load from dropping in the unlikely event that the spring breaks.